

LSI LOGIC

Providing Maximum Throughput for External RAID and Non-RAID Storage Arrays

Key Advantages

- Flexible SAS/SATA array architecture optimizes cost
- Eight external high-speed SAS ports for maximum mass-storage connectivity
- 3Gb/s per port delivers 2400 MB/s to external enclosures
- MyStorage management software simplifies large-scale tiered storage arrays
- SAS/SATA interconnect proven through LSI Logic's robust serial technology

Industry's First 8-port External SAS Controller

The LSI SAS3800X card enables large-scale direct attach storage (DAS) arrays through eight external 3Gb/s ports, driving up to 122 Serial Attached SCSI (SAS) and Serial ATA (SATA) devices. The host bus adapter supports large capacity external server storage RAID and non-RAID enclosures by connecting a 64-bit PCI-X 133MHz bus with two external x4 SFF-8470 SAS connectors. The SAS3800X demonstrates a significant advantage over parallel SCSI in providing 2400MB/s external data throughput and cost optimization of SAS and SATA drives.

Cost-Optimization of External Storage with SAS

As the first-to-market leader in SAS, LSI is providing more bandwidth to cost-optimized external drive arrays. System integrators can use the SAS3800X to build large-scale storage array infrastructures that supports both SAS and SATA devices. By utilizing lower-cost SATA drives for data backup and SAS drives for mission-critical applications, end-users will receive high-capacity, high-performance data storage while enjoying an interrupt-free high-activity environment. The performance advantage and cost savings can be felt immediately when using the SAS3800X to develop and tiered storage array.



Unsurpassed Host bus and SAS/SATA Signal Quality

LSI has been the hands-down leader in serial interface technology for over five generations. The SAS3800X HBA leverages LSI's expertise in serial communication to provide superior signal integrity over distances greater than 6 meters. Security in data transmission over long distances enables the SAS3800X to supply more external storage applications without needing a high-cost optical infrastructure. Additionally LSI's high-speed serial interconnect expertise ensures an interrupt-free, READ/WRITE intensive experience for end-users.

MyStorage™ – Simple Storage Array Management

Managing several drives in a storage array can be difficult when running a mixture of SAS and SATA. LSI's MyStorage management software makes storage array optimization easy. MyStorage fully automates the task of deploying and maintaining server to storage array connectivity. From the most modest, small-scale DAS replacement to an ambitious data center, MyStorage keeps it simple.

Through an intuitive Graphical User Interface (GUI), this powerful utility helps customers manage storage quickly and easily. Using MyStorage, users can inspect and control all LSI Logic adapters with point and click simplicity. A rich suite of tools enables remote firmware update, drive monitoring, link tuning, load balancing, path monitoring, diagnostics and error reporting. Altogether, MyStorage delivers a complete set of management tools that are simple to use.

APPLICATIONS

- High performance workstations
- Mid to high-end servers
- External and internal storage connections

TYPICAL USES

- Large-scale external RBOD enclosures
- Tiered SAS/SATA RAID arrays
- Mission-critical applications running from SAS drives

FEATURES

- 3Gbps per port
- 2 x4 external SFF8470 connectors
- Full-height HBA
- Connects to both SAS and SATA HDDs and tape drives
- Allows more than 122 total end-point devices
- Fusion-MPT architecture providing over 140,000 I/Os per second
- Supports all major OSes



LSI SAS3800X

3GB/S SAS 8-PORT HOST BUS ADAPTER

Operating System Support

The SAS3800X HBA supports all key 32-bit and 64-bit versions of Microsoft Windows, Linux, Solaris, Netware as well as the x86, IA64, SPARC, AMD64 and EM64T system architectures. All OS drivers are backed by extensive testing and validation to ensure optimum system performance. For a list of the most current supported drivers, visit www.lsillogic.com/support.

TECHNICAL SPECIFICATIONS

PCI Bus	64-bit, 133MHz PCI-X, backward compatible with PCI	
PCI Modes	Bus master DMA	
PCI Data Burst Transfer Rates	132MB/s (PCI 32-bit bus @ 33MHz) 264MB/s (PCI 64-bit bus @ 33MHz) 528MB/s (PCI 64-bit bus @ 66MHz) 800MB/s (PCI-X 64-bit bus @ 100MHz) 1064MB/s (PCI-X 64-bit bus @ 133MHz)	
SAS Bandwidths	Half Duplex Single lane – 300MB/s 2-lanes – 600MB/s 3-lanes – 900MB/s 4-lanes – 1200MB/s 8-lanes – 2400MB/s	Full Duplex Single SAS lane – 600MB/s 2-lanes – 1200MB/s 4-lanes – 2400MB/s
PCI Card Type	3.3V add-in card	
PCI Voltage	+3.3V ±0.3V	
PCI Form Factor	6.6" x 3.8"	
PCI Power	7.5W	
Bracket	Full height	
Certification Level	PCI 2.2, PCI-X 1.0a, PCI-X 2.0 model	
SAS Bus	Eight external 3GB/s SAS/SATA ports	
SAS Processor	LSISAS1068	
Connectors	External 2 SFF-8470 SAS connectors	
LED Indicators	Internal Activity per Phy 4	Internal Fault per Phy 4
Max No. of Physical Devices	122	
Environments	Operating 0°C to 60°C 5 to 90% non-condensing	Storage -45°C to +105°C 5 to 90% non-condensing
MTBF	>200,000 hours	
Compliances	EMC: Class B-US (CFR 47, P15B); Canada (ICES-003); Japan (V-3/02.04) Europe (EN55022/EN55024); Australia/New Zealand (AS/NZS 3548); Safety: EN60950	
Software: MyStorage	Drive monitoring, HBA management, drive topology	
OS Support	<ul style="list-style-type: none">• Microsoft™ Windows® 2000, Server 2003 32-bit (x86 and AMD64), XP• Red Hat® Linux® RHEL 3• Novell® NetWare®• SuSE® Linux®/SLES• Sun SPARC Solaris 2.6 thru 2.10	
Support		
Ordering Information	SAS3800X kit P/N: LSI00056 SAS3800X 5-pack P/N: LSI00057	
Warranty	3 years, advanced replacement option	
Technical Support	Free technical support: http://www.lsi.com/support	

Visit the LSI Logic web site at:
<http://lsilogic.com/storage>

LSI Logic NA Headquarters
+1 866-574-5741
<http://lsilogic.com>

North American
Storage Adapter Sales
+1 877-LSI-LOGIC
(+1 877-574-5644)

[http://www.lsillogic.com/products/
storage_adapters/](http://www.lsillogic.com/products/storage_adapters/)
Advanced Technical Support
North / South America
+1 800-633-4545
+1 678-728-1250
<http://lsilogic.com/support>
support@lsil.com

LSI Logic European Headquarters
+44 1344-413200

UK / Ireland / Nordic Region /
South Africa
+44 1344-413115

France / Spain / Portugal
+33 14601-1340

Belgium / Netherlands / Luxembourg
+31 402-96-2111

Italy +39 039-687-3705

Central / Eastern Europe
+49 89-45833-312

Israel +49 89-458-33-342

Europe Advanced Technical Support

English +44 1344-413-441

Deutsch +49 89-45833-338

<http://lsilogic.com/support>
eurosupport@lsil.com

All Other EMEA

+49 89-45833-156

LSI Logic

Pacific Asia Headquarters

Taiwan +866 2-2718-7828

Tokyo +81 3-5463-7821

Korea +82 2528-3400

Hong Kong +852 2192-1789

Singapore / South Pacific

+65 6334-9080

LSI Logic, the LSI Logic logo design, Fusion-MPT, Integrated RAID, and MyStorage are trademarks or registered trademarks of LSI Logic Corporation. All other brand and product names may be trademarks of their respective companies. LSI Logic Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI Logic does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI Logic; nor does the purchase, lease, or use of a product or service from LSI Logic convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI Logic or of third parties.

Printed 3/06 USA. All rights reserved.
10036

© LSI Logic Corporation 2006.