

Product

E10G18-T1



Hardware Specifications

General	
Host Bus Interface	PCIe 3.0 x4
Bracket Height	Low Profile and Full Height
Size (Height x Width x Depth)	86.0 mm x 68.1 mm x 13.6 mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-5°F to 140°F)
Relative Humidity	5% to 95% RH
Warranty	5 Years
Notes	The warranty period starts from the purchase date as stated on your purchase receipt. (Learn more)

Network	
IEEE Specification Compliance	<ul style="list-style-type: none">• IEEE 802.3x Flow Control• IEEE 802.3u Fast Ethernet• IEEE 802.3ab Gigabit Ethernet• IEEE 802.3bz 2.5Gbps / 5Gbps Ethernet• IEEE 802.3an 10Gbps Ethernet
Data Transfer Rates	10 Gbps
Network Operation Mode	Full Duplex
Supported Features	<ul style="list-style-type: none">• 9 KB Jumbo Frame• TCP/UDP/IP Checksum Offloading• Auto-negotiation between 100Mb/s, 1Gb/s, 2.5Gb/s, 5Gb/s, and 10Gb/s

Compatibility

Applied Models

- FS series:FS6400, FS3600, FS3410, FS3400, FS3017, FS2500, FS2017, FS1018
- SA series:SA6400, SA3610, SA3600, SA3410, SA3400D, SA3400, SA3200D
- UC series:UC3400, UC3200
- 23 series:RS2423RP+, RS2423+, DS1823xs+
- 22 series:RS822RP+, RS822+, DS3622xs+, DS2422+
- 21 series:RS4021xs+, RS3621xs+, RS3621RPxs, RS2821RP+, RS2421RP+, RS2421+, RS1221RP+, RS1221+, DS1821+, DS1621xs+, DS1621+
- 20 series:RS820RP+, RS820+
- 19 series:RS1619xs+, RS1219+, DS2419+II, DS2419+, DS1819+
- 18 series:RS3618xs, RS2818RP+, RS2418RP+, RS2418+, RS818RP+, RS818+, DS3018xs, DS1618+
- 17 series:RS18017xs+, RS4017xs+, RS3617xs+, RS3617RPxs, RS3617xs, DS3617xsII, DS3617xs, DS1817+, DS1517+
- 16 series:RS18016xs+
- 15 series:RC18015xs+, DS3615xs
- 14 series:RS3614xs+, RS3614RPxs, RS3614xs
- 13 series:RS10613xs+, RS3413xs+
- 12 series:RS3412RPxs, RS3412xs, DS3612xs
- 11 series:RS3411RPxs, RS3411xs, DS3611xs

Notes

DSM version requirement: 6.2-23739-2 onward (or 6.1-15284-2 onward with DSM 6.1)
